



Case	
Dimensions case (lxwxh) [mm]	630 x 500 x 180
Dimensions case with trolley installation (lxwxh) [mm]	630 x 630 x 300
Weight [kg]	15
Material	Aluminium with foam inlay
Content	
Compact flame scanner F300K	TYPE UV-1; with integral user interface
Compact flame scanner F300K	TYPE UV-4; with LED display
External user interface FB30-00	with connecting cable
Compact flame scanner F200K	TYP 2 UV-2; screwing housing
Flame monitor F152	
Flame sensor FFS07	TYP UV-1; with connecting 3 m approx.
Flame sensor FFS08	TYP IR-1 T; with connecting 2 m approx.
Flame scanner testing device FFP30	for UV and IR



Die Angaben in dieser Druckschrift gelten vorbehaltlich technischer Änderungen.

**LAMTEC Meß- und Regeltechnik**  
für Feuerungen GmbH & Co. KG

Wiesenstraße 6  
D-69190 Walldorf  
Telefon: +49 (0) 6227 / 6052-0  
Telefax: +49 (0) 6227 / 6052-57  
E-Mail: info@lamtec.de  
www.lamtec.de

**LAMTEC Leipzig GmbH & Co. KG**

Portitzer Straße 69  
D-04425 Taucha  
Telefon: +49 (0) 34298 / 4875-0  
Telefax: +49 (0) 34298 / 4875-99

**Überreicht durch:**

Druckschrift-Nr. DLT7667-EN-001  
Printed in Germany